



EU-TYPE EXAMINATION CERTIFICATE



The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/3431/162/02/20/0630

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer : P2L
13 Rue Sainte Odile 67520 Marlenheim
France

Description

PPE Type : *protective glove against mechanical risks*
Product reference : G34300
Article code :
Glove description : 15G nylon liner, Black microfoam nitrile 3/4 coating
Available sizes : 6 7 8 9 10 11

Pictures :



CTC certifies only PPE which meets requirements of the PPE European Regulation 2016/425

Reference standard :

Levels of performance / class of protection

EN 420:2003+A1:2009

-

EN 388:2016 + A1:2018

4 1 2 1 X

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 01 dated from MARCH 2020

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425.

Issued in Lyon by
Maxence DREVET
Project Certification Manager

Date of first issue : 02 March 2020
End of validity date : 02 March 2025



In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC.



Accreditation n° 5-0594
Scope available on:
www.cofrac.fr

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France
Tél. : +33 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com

Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie
Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

P2L

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product	:	G34300
Article code	:	
Technical file index	:	01
Last update	:	MARCH 2020

IDENTIFICATION

Reference of the product : : G34300
Article code : :
Basic Model : :
Technical file index : : 01
Last update : : MARCH 2020

Manufacturer :

P2L

13 Rue Sainte Odile 67520 Marlenheim

France

tel : 33(0) 3.88.04.68.67

fax : 33(0) 3.26.00.73.48

Factory :

NANTONG QIANGSHENG SAFETY PROTECTION TECHNOLOGY INCORPORATED
COMPANY

No.118, JIALINGJIANG ROAD, RUDONG ECONOMIC DEVELOPMENT ZONE,
JIANGSU PROVINCE, P.R. CHINA

CHINA

tel: 86-513-4108356

fax: 86-513-4108190

NANTONG QIANGSHENG SAFETY PROTECTION TECHNOLOGY CO, LTD.
YOUYI ROAD (W), JUEGANG, RUDONG JIANGSU

CHINA

tel: 86-513-4108356

fax: 86-513-4108190

NANTONG QIANGSHENG SAFETY PROTECTION TECHNOLOGY CO, LTD.
JINSHAJIANG ROAD, NEW INDUSTRIAL ZONE, RUDONG, JIANGSU

CHINA

tel: 86-513-84129800

fax: 86-513-84129808

NANTONG QIANGSHENG SAFETY PROTECTION TECHNOLOGY CO, LTD.
JINSHAJIANG ROAD, JUEGANG, RUDONG JIANGSU

CHINA

tel: 86-513-84129800

fax: 86-513-84129808

GLOVE DESCRIPTION

General glove description :

15G nylon liner, Black microfoam nitrile 3/4 coating
type of coating finish : foam

Visual description (picture back and palm sides) :



Field of use

Protective gloves against mechanical risk, used in industry; for automotive industry; Aerospace, Automotive manufacturing, construction, logistics, packaging, plastic injection molding

Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)

		Applicable	Covered by
§1	Requirements defined in the Annex II §1 are applicable to all PPE	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§1.4	Manufacturer's instructions and information is available	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.5	PPE which may be caught up during use	<input checked="" type="checkbox"/>	<input type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input type="checkbox"/> Marking
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking
§3.3	The PPE is intended to protect against mechanical injuries	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/> Standard <input checked="" type="checkbox"/> Instruction for use <input checked="" type="checkbox"/> Marking

Available sizes :

Minimum length of glove (mm)	Sizes
220mm	6
230mm	7
240mm	8
250mm	9
260mm	10
270mm	11

Glove constitution :

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm		BLACK	NITRILE			0.85-1.5MM
		GREY	NYLON	500g/m2	15	
Back	3/4 coating	BLACK	NITRILE			0.85-1.5MM
		GREY	NYLON	500g/m2	15	
Cuff		GREY	NYLON/ELASTIC	550g/m2	15	
Binding		White/ red/ yellow/ brown/ blue/ purple/ grey/ orange/ black/ green	Polyester			

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.
This glove is designed against mechanical risks.
It is a category II product.

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : 5
Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACH regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2016 + A1 : 2018

Protection offered	Performance levels
Abrasion resistance	4
Blade cut resistance	1
Tear strength resistance	2
Puncture resistance	1
Cut Resistance method (EN ISO 13997)	X
Impact Protection	-

The levels of performance have been measured on the palm

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.


TEST REPORTS

Laboratory	CTC	Other
EN 420 + innocuousness	S190607911_1 S170506854_1 S170607562_1 S171114558_1 S170810908_1 S171114556_1 S171114555_1 S171216550_1 H170903808_1 S171114552_1 S171114553_1 S171114554_1 S171114557_1 S171217274_1 S181216899_1(DMFu)	
EN 388	S190607910_1 S170506854_1	

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer :

Logo 

Glove's reference : G34300

Article Code :

Size indicator

Pictograms related to risks against which protection is offered with performance levels

Information pictogram

Address of Manufacturer :

Date of Manufacture (month/year) and/or Serial number :

Marking example :



Method of marking on the glove :

Heat transfer AND SEWN LABEL

Packaging :

EACH PAIR PER POLYBAG, 1 DOZEN PER BIG POLYBAG, 5 DOZENS PER CARTON

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean , ventilated, light).

Declaration of conformity :

Available on : <http://www.p2l.fr>

MEANS OF CONTROL

We make all inspection based on the acceptance sampling. Materials Conduct inspection on all incoming raw materials and accessory materials. Conduct size checking on all component parts. Conduct visual inspection on defective parts. Checking missing parts before sending to sewers. Inspected for defects, gauged for proper thickness. Quality checking on sewing in areas of appearance, sizing(based on the EN420 sizing standard), weight,labelling, stitches, seaming and component positioning. After coating we will make the sizing, weight,smell,PH,chemic test and cutting ,abrasion test (based on EN388 standard) every one year. Finished Products perform random checking(acceptance sampling) before shipment. Quality control is performed under ISO 9001.

DAS CERTIFICATION



**Quality Management System
Certificate of Approval**
This is to certify that the QMS of

Nantong Qiangsheng Safety Protection Technology Incorporated Company
Unified Social Credit Code:913206237910735121

No.118, Jialingjiang Road, Rudong Economic Development Zone, Jiangsu Province, P.R.China

Has been assessed and found to meet the requirements of
GB/T 19001-2016/ISO 9001:2015
This certificate is valid for the following scope of operations:

**Manufacture and Service of Special Fiber Gloves, Nylon Gloves, Yarn Gloves, Dipping Glue
Gloves, Leather Gloves for Safety Protection Using**

Date of Certificate Issue: 21, July, 2017
Certificate Valid Until: 20, July, 2020
Certificate Number: **Q041707115**

The validity of the registration will be continued only when the organisation pass the annual surveillance audit.
Check the validity of certificate at www.cnca.gov.cn or www.das-china.com
Surveillance Audits:

Authorized by:  Chief Executive



Shanghai DAS Certification Co., Ltd. , member of SN Registrars(Holdings) Ltd.
Add:505, Tower 2, Guosun Center, No. 388, Zhongjiang Road, Shanghai, P.R.China, 200062
Tel: 0086-21-62773910 Fax:0086-21-62080319
Web:<http://www.das-china.com>
Email: info@das-china.com
UK Head Office: DAS Certification Limited (On Behalf of SN Registrars (Holdings) Limited)
ADD: Registration House, 22b Church Street, Rushden, Northamptonshire, NN10 9YT, UK
Tel: +44(0)1933 381859
Email: info@dascertification.co.uk
Web: www.dascertification.co.uk
Company Number: 07659067



INSTRUCTION FOR USE

P2L

13 Rue Sainte Odile 67520 Marlenheim

France

Glove reference : G34300

Article code:

User notice index : 01

Last update : MARCH 2020

Available sizes : 6 7 8 9 10 11



Glove description :

15G nylon liner, Black microfoam nitrile 3/4 coating

THIS GLOVE IS A PERSONAL PROTECTIVE EQUIPMENT BELONGING TO THE CATEGORY II.

It meets the requirements of the PPE Regulation 2016/425 applicable from April 21th, 2018 : innocuousness, comfort, solidity.

It has been subject to a UE-type Examination performed by :

C.T.C. (0075)
4, rue Hermann Frenkel
69367 LYON Cedex 07
FRANCE

Applicable standards :

The glove meets the requirements of the standard EN 420 : 2003 + A1 : 2009 « General requirements for work glove ». Dexterity : 5

Moreover, this glove has been designed for the following applications :

Application :

Mechanical hazard - EN 388 : 2016 +
A1:2018



4 1 2 1 X

Levels of performance

Abrasion resistance	4	(on 4 maxi)
Blade cut resistance	1	(on 5 maxi)
Tear resistance	2	(on 4 maxi)
Puncture resistance	1	(on 4 maxi)
Cut Resistance method (EN ISO 13997)	X	(A to F)
Impact Protection		

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

Protection limit :

Users should be warned that gloves should not be worn when there is a risk of entanglement by moving parts of machines.

This model does not contain any substances at levels that are known to, or suspected to, adversely affect user hygiene or health.

The protection against risks or hazards which are not mentioned in this document is not warranted.

The levels of performance mentioned are only valid for the palm of the glove.

The levels of performance mentioned are only valid for new gloves, not washed, nor regenerated.

These levels of performance are obtained from the tests done according to conditions defined by the applicable standards.

This glove shall not be in contact with fire

Before use, the glove shall be visually controlled, in case of deterioration the gloves must be scrapped (abrasion, cut, tear, ...).

For gloves with different layers of material, the performance levels are warranted only for the whole glove.

For gloves with two or more layers the overall classification does not necessarily reflect the performance of the outermost layer.

Storage and cleaning notice

Keep in its original packaging, under ordinary temperature and humidity conditions and in clean, covered and ventilated premises.

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity :

Available on : <http://www.p2l.fr>